



上海晟芯微电子有限公司

Shanghai Senchip Microelectronics Co., Ltd

Electro-static Discharge (ESD)

SESD5D12V

Features

- 200 Watts peak Power Line($t_p = 8/20\mu s$)
- Replacement for MLV(0603)
- Protects one I/O or power line
- Low clamping voltage
- Low leakage current
- Response Time is Typically $< 1ns$



IEC COMPATIBILITY (EN61000-4)

- IEC 61000-4-2 (ESD) $\pm 15kV$ (air), $\pm 8kV$ (contact)
- IEC 61000-4-4 (EFT) 40A (5/50ns)


Mechanical Characteristics

- JEDEC SOD-523 package
- Molding compound flammability rating:
UL 94V-0
- Marking : Marking Code
- Packaging : Tape and Reel per EIA 481
- RoHS/WEEE Compliant

Applications

- Cellular Handsets & Accessories
- Personal Digital Assistants (PDAs)
- Notebooks & Handhelds
- Portable Instrumentation
- Digital Cameras
- MP3 players

Schematic & PIN Configuration



SOD-523 (Top View)




上海晟芯微电子有限公司

Shanghai Senchip Microelectronics Co., Ltd

Absolute Maximum Rating			
Rating	Symbol	Value	Units
Peak Pulse Power($t_P=8/20 \mu s$)	PPP	200	Watts
Peak Forward Voltage($I_F=1A$, $t_P=8/20 \mu s$)	VFP	1.4	V
Operating Temperature	TJ	-55to+125	°C
Storage Temperature	TSTG	-55to+150	°C

Electrical Parameters (T=25°C)

Symbol	Parameter
I _{PP}	Maximum Reverse Peak Pulse Current
V _C	Clamping Voltage @ I _{PP}
V _{RWM}	Working Peak Reverse Voltage
I _R	Maximum Reverse Peak Pulse Current @ V _{RWM}
V _{BR}	Breakdown Voltage @ I _T
I _T	Test Current
I _F	Forward Current
V _F	Forward Voltage @ I _F



Electrical Characteristics

Part No.	V _{RWM} (V)	I _R (μA)	V _{BR} (V)	C(PF)	P _{PK} (W)	Package
SESD5D12V	12.0	1.0	12.5-15.7	50	200	SOD523



Typical Characteristics

Figure 1: Peak Pulse Power Vs Pulse Time




Figure 2: Power Derating Curve




Figure 3: Clamping Voltage vs. Peak Pulse Current




Figure 4: Normalized Junction Capacitance vs. Reverse Voltage




Figure 5: Pulse Waveform






Figure 6: ESD Clamping(8kV Contact per IEC 61000-4-2)



Outline Drawing – SOD-523



CONTACT INFORMATION

Add: Room 729, Saiger Science Park Building 2 east, Futian District, Shenzhen, Guangdong.

Tel: 0755-82045978-810

Fax: 0755-82044903-803