

70

Axial fan
× 70 × 25mm



General Specifications

- Motor : 4 Poles brushless DC motor
- Frame & Impeller : Plastic(UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

Major Characteristic Parameters

品牌	轴承	电压	启动电压	频率	电流	功率	转速	风量	静压	燥音		
型号	B/S	V	V	HZ	A	W	RPM	m3/min	CFM	mm-H2O	In-H2O	dba
SP70B11L-25AL	B/S	110	98/264	50/60	0.03	2.00	2500	0.55	19.70	1.90	0.07	24.0
SP70B11M-25AL	B/S	110	98/264	50/60	0.04	3.00	3000	0.67	23.70	3.10	0.12	28.0
SP70B11H-25AL	B/S	110	98/264	50/60	0.05	4.00	3500	0.78	27.60	3.80	0.15	33.0
SP70B22L-25AL	B/S	220	98/264	50/60	0.03	2.00	2500	0.55	19.70	1.90	0.07	24.0
SP70B22M-25AL	B/S	220	98/264	50/60	0.04	3.00	3000	0.67	23.70	3.10	0.12	28.0
SP70B22H-25AL	B/S	220	98/264	50/60	0.05	4.00	3500	0.78	27.60	3.80	0.15	33.0

*Bearing system B: Two Ball Bearing S: Sleeve Bearing

