

尺寸	轴承	电压	电流	功率	转速	风量		静压		噪音
规格	B/S	V	A	W	RPM	m <sup>3</sup> /mi n	CFM	mm-H2O	In-H2O	dba
60×60×25mm	B/S	110	0.03~0.05	2.00~4.00	3000~5500	0.39~0.71	13.80~25.20	2.30~6.50	0.09~0.25	24.0~37.0
70×70×25mm	B/S	110	0.03~0.05	2.00~4.00	2500~3500	0.55~0.78	19.70~27.60	1.90~3.80	0.07~0.15	24.0~33.0
80×80×25mm	B/S	110	0.03~0.05	3.00~5.00	2400~3200	0.85~1.20	30.20~42.50	2.20~4.30	0.08~0.16	23.0~34.0
80×80×38mm	B/S	110	0.03~0.06	3.00~6.00	2500~3500	0.98~1.37	34.80~48.70	4.20~8.20	0.16~0.32	32.0~42.0
92×92×25mm	B/S	110	0.03~0.06	3.00~6.00	2000~2800	1.11~1.56	39.40~55.20	1.50~3.00	0.05~0.11	25.0~33.0
92×92×38mm	B/S	110	0.03~0.07	5.00~7.00	2500~3500	1.61~2.26	57.10~79.90	4.20~8.90	0.16~0.35	29.0~37.0
120×120×25mm	B/S	110	0.05~0.08	3.00~7.00	1800~2600	1.94~2.83	68.60~100.20	2.10~4.20	0.08~0.16	28.0~38.0
120×120×38mm	B/S	110	0.06~0.13	6.00~18.00	2500~4000	2.82~4.76	99.70~168.20	5.80~14.20	0.22~0.56	40.0~50.0
150×150×50mm	B/S	110	0.18~0.35	16.00~35.00	2500~3500	5.24~7.36	185.20~260.00	9.40~18.50	0.37~0.73	44.0~59.0
172×150×51mm	B/S	110	0.18~0.35	16.00~35.00	2500~3500	5.24~7.36	185.20~260.00	9.40~18.50	0.37~0.73	44.0~59.0
200×200×60mm	B	110	0.20~0.40	25.00~45.00	2000~2500	13.88~15.07	490.00~532.00	15.50~18.80	0.61~0.74	50.0~58.0
224×89mm	B	110	0.45~0.48	33.00~52.00	2100~2500	15.38~20.30	543~718	21.66~25.50	0.85~1.01	51.4~68.2