

| 尺寸           | 轴承  | 电压  | 电流        | 功率          | 转速        | 风量                   |               | 静压          |           | 噪音        |
|--------------|-----|-----|-----------|-------------|-----------|----------------------|---------------|-------------|-----------|-----------|
| 规格           | B/S | V   | A         | W           | RPM       | m <sup>3</sup> /mi n | CFM           | mm-H2O      | In-H2O    | dba       |
| 60×60×25mm   | B/S | 220 | 0.03~0.05 | 2.00~4.00   | 3000~5500 | 0.39~0.71            | 13.80~25.20   | 2.30~6.50   | 0.09~0.25 | 24.0~37.0 |
| 70×70×25mm   | B/S | 220 | 0.03~0.05 | 2.00~4.00   | 2500~3500 | 0.55~0.78            | 19.70~27.60   | 1.90~3.80   | 0.07~0.15 | 24.0~33.0 |
| 80×80×25mm   | B/S | 220 | 0.03~0.05 | 3.00~5.00   | 2400~3200 | 0.85~1.20            | 30.20~42.50   | 2.20~4.30   | 0.08~0.16 | 23.0~34.0 |
| 80×80×38mm   | B/S | 220 | 0.03~0.06 | 3.00~6.00   | 2500~3500 | 0.98~1.37            | 34.80~48.70   | 4.20~8.20   | 0.16~0.32 | 32.0~42.0 |
| 92×92×25mm   | B/S | 220 | 0.03~0.06 | 3.00~6.00   | 2000~2800 | 1.11~1.56            | 39.40~55.20   | 1.50~3.00   | 0.05~0.11 | 25.0~33.0 |
| 92×92×38mm   | B/S | 220 | 0.03~0.07 | 5.00~7.00   | 2500~3500 | 1.61~2.26            | 57.10~79.90   | 4.20~8.90   | 0.16~0.35 | 29.0~37.0 |
| 120×120×25mm | B/S | 220 | 0.05~0.08 | 3.00~7.00   | 1800~2600 | 1.94~2.83            | 68.60~100.20  | 2.10~4.20   | 0.08~0.16 | 28.0~38.0 |
| 120×120×38mm | B/S | 220 | 0.06~0.13 | 6.00~18.00  | 2500~4000 | 2.82~4.76            | 99.70~168.20  | 5.80~14.20  | 0.22~0.56 | 40.0~50.0 |
| 150×150×50mm | B/S | 220 | 0.18~0.35 | 16.00~35.00 | 2500~3500 | 5.24~7.36            | 185.20~260.00 | 9.40~18.50  | 0.37~0.73 | 44.0~59.0 |
| 172×150×51mm | B/S | 220 | 0.18~0.35 | 16.00~35.00 | 2500~3500 | 5.24~7.36            | 185.20~260.00 | 9.40~18.50  | 0.37~0.73 | 44.0~59.0 |
| 200×200×60mm | B   | 220 | 0.20~0.40 | 25.00~45.00 | 2000~2500 | 13.88~15.07          | 490.00~532.00 | 15.50~18.80 | 0.61~0.74 | 50.0~58.0 |
| 224×89mm     | B   | 220 | 0.45~0.48 | 33.00~52.00 | 2100~2500 | 15.38~20.30          | 543~718       | 21.66~25.50 | 0.85~1.01 | 51.4~68.2 |