

品牌	轴承	电压	启动电压	电流	功率	转速	风量		静压	噪音	
型号	B/S	V	V	A	W	RPM	m ³ /mi n	CFM	mm-H2O	In-H2O	dba
SP02007_05L	S	5	4.5~5.5	0.07	0.35	7000	0.01	0.35	1.10	0.04	22.3
SP02007_05M	S	5	4.5~5.5	0.09	0.45	10000	0.02	0.71	1.90	0.07	29.0
SP02007_05H	S	5	4.5~5.5	0.11	0.55	13000	0.03	1.06	3.20	0.12	32.0
SP02010_05L	S/B	5	4.5~5.5	0.10	0.50	9000	0.02	0.60	1.94	0.08	20.0
SP02010_05M	S/B	5	4.5~5.5	0.15	0.75	12000	0.02	0.83	2.22	0.09	27.1
SP02010_05H	S/B	5	4.5~5.5	0.20	1.00	18000	0.03	1.22	5.22	0.21	37.2
SP02507_05L	S/B	5	4.5~5.5	0.12	0.60	6000	0.02	0.88	1.40	0.05	18.0
SP02507_05M	S/B	5	4.5~5.5	0.13	0.65	7000	0.04	1.32	1.90	0.07	20.0
SP02507_05H	S/B	5	4.5~5.5	0.16	0.80	10000	0.05	1.85	4.40	0.17	23.5
SP02507_05U	S/B	5	4.5~5.5	0.22	1.10	13000	0.07	2.41	7.30	0.29	28.0
SP02510_05L	S/B	5	4.5~5.5	0.12	0.60	6000	0.02	0.88	1.40	0.05	18.0
SP02510_05M	S/B	5	4.5~5.5	0.13	0.65	7000	0.04	1.32	1.90	0.07	20.0
SP02510_05H	S/B	5	4.5~5.5	0.16	0.80	10000	0.05	1.85	4.40	0.17	23.5
SP02510_05U	S/B	5	4.5~5.5	0.22	1.10	13000	0.07	2.41	7.30	0.29	28.0
SP03007_05L	S	5	4.5~5.5	0.13	0.65	5000	0.05	0.79	1.30	0.05	22.5
SP03007_05M	S	5	4.5~5.5	0.17	0.85	8000	0.08	2.68	1.90	0.08	28.6
SP03007_05H	S	5	4.5~5.5	0.25	1.25	11000	0.11	3.92	2.90	0.11	32.6
SP03007_05U	S	5	4.5~5.5	0.32	1.60	13000	0.12	4.25	3.58	0.14	36.8
SP03010_05L	S/B	5	4.5~5.5	0.10	0.50	5800	0.07	2.56	2.59	0.10	21.5
SP03010_05M	S/B	5	4.5~5.5	0.15	0.75	8500	0.11	3.46	3.76	0.14	26.5
SP03010_05H	S/B	5	4.5~5.5	0.17	0.85	10500	0.12	4.30	4.48	0.17	29.2
SP03010_05U	S/B	5	4.5~5.5	0.22	1.10	13000	0.16	5.56	5.89	0.23	33.5
SP03510_05L	S/B	5	4.5~5.5	0.05	0.25	5000	0.06	2.10	1.80	0.07	18.0
SP03510_05M	S/B	5	4.5~5.5	0.06	0.30	6000	0.08	2.72	2.60	0.10	20.0
SP03510_05H	S/B	5	4.5~5.5	0.07	0.35	7000	0.14	4.96	3.50	0.14	23.0
SP03510_05U	S/B	5	4.5~5.5	0.08	0.40	8000	0.16	5.51	4.50	0.18	25.0
SP03510_05V	S/B	5	4.5~5.5	0.10	0.50	9000	0.18	6.30	5.50	0.22	28.0
SP04010_05L	S/B	5	4.5~5.5	0.09	0.45	4000	0.11	3.91	1.80	0.07	21.0
SP04010_05M	S/B	5	4.5~5.5	0.13	0.65	5000	0.15	5.30	2.70	0.11	25.0
SP04010_05H	S/B	5	4.5~5.5	0.16	0.80	6000	0.18	6.36	3.90	0.15	29.0
SP04010_05U	S/B	5	4.5~5.5	0.22	1.10	7000	0.22	7.92	4.60	0.18	33.0
SP04015_05L	S/B	5	4.5~5.5	0.12	0.60	4000	0.16	5.80	3.35	0.13	18.9
SP04015_05M	S/B	5	4.5~5.5	0.21	1.05	6000	0.23	8.13	5.12	0.20	25.3