

尺寸	轴承	电压	启动电压	电流	功率	转速	风量		静压		噪音
规格	B/S	V	V	A	W	RPM	m ³ /mi n	CFM	mm-H2O	ln-H2O	dba
20×20×07mm	S	5/12	7.0~13.2	0.06~0.09	0.72~1.08	7000~13000	0.01~0.03	0.35~1.06	1.1~3.2	0.04~0.12	22.3~32.0
20×20×10mm	B/S	5/12	7.0~13.2	0.07~0.15	0.35~0.75	9000~18000	0.02~0.03	0.60~1.22	1.94~5.22	0.08~0.21	20.0~37.2
25×25×07mm	B/S	5/12	7.0~13.2	0.06~0.12	0.36~0.12	7000~15000	0.035~0.080	1.22~2.81	2.16~4.50	0.085~0.177	19.6~31.2
25×25×10mm	B/S	5/12	7.0~13.2	0.03~0.10	0.36~1.20	7000~15000	0.034~0.084	1.21~2.98	4.18~7.98	0.085~0.314	19.6~28.9
30×30×07mm	B/S	5/12	7.0~13.2	0.04~0.12	0.48~1.44	5000~13000	0.05~0.12	0.79~4.25	1.30~3.58	0.05~0.14	22.5~36.80
30×30×10mm	B/S	5/12	7.0~13.2	0.02~0.12	0.24~1.44	5800~13000	0.05~0.12	1.88~4.22	43.6~9.77	0.10~0.23	23.2~34.2
35×35×10mm	B/S	5/12	7.0~13.2	0.03~0.07	0.36~0.84	7000~9000	0.14~0.18	4.96~6.30	3.50~5.50	0.14~0.22	23.0~28.0
40×40×10mm	B/S	5/12/24	7.0~13.2	0.05~0.14	0.60~1.68	4000~8000	0.11~0.26	3.91~9.05	1.80~6.00	0.07~0.24	21.0~38.0
40×40×15mm	B/S	5/12/24	7.0~13.2	0.05~0.19	0.60~2.88	4000~10000	0.16~0.38	5.80~13.60	3.40~12.30	0.13~0.48	18.9~39.6
40×40×20mm	B/S	5/12/24	7.0~13.2	0.10~0.22	1.20~2.64	5000~9500	0.21~0.31	7.4~11.6	4.8~11.9	0.19~0.47	21.0~33.5
40×40×28mm	B/S	5/12/24	7.0~13.2	0.18~0.70	2.16~8.40	8000~15000	0.39~0.70	13.90~24.80	11.60~41.6	0.46~1.64	40.0~58.0
45×45×10mm	B/S	5/12/24	7.0~13.2	0.07~0.08	0.84~0.96	5000~7000	0.31~0.41	10.64~14.15	3.22~5.51	0.13~0.24	30.2~38.4
50×50×10mm	B/S	5/12/24	7.0~13.2	0.05~0.10	0.60~1.20	3500~6500	0.19~0.36	6.70~12.70	1.40~4.50	0.05~0.18	18.0~35.0
50×50×15mm	B/S	5/12/24	7.0~13.2	0.10~0.21	1.20~2.52	4000~6400	0.28~0.45	10.00~15.80	2.80~7.00	0.11~0.27	24.0~36.0
50×50×20mm	B/S	5/12/24	7.0~13.2	0.06~0.14	0.72~2.16	4000~6400	0.31~0.52	10.98~18.30	2.42~6.44	0.10~0.25	25.0~37.0
60×60×10mm	B/S	5/12/24	7.0~13.2	0.13~0.24	1.56~2.88	3500~4900	0.49~0.69	17.40~24.30	2.10~4.10	0.08~0.16	28.0~37.0

60×60×15mm	B/S	5/12/24	7.0~13.2	0.06~0.14	0.72~1.68	3000~5000	0.43~0.75	15.0~26.5	2.30~5.70	0.09~0.23	24.0~37.0
60×60×20mm	B/S	5/12/24	7.0~13.2	0.07~0.17	0.84~2.04	3200~4800	0.38~0.56	13.50~19.60	3.00~6.90	0.12~0.27	24.0~33.0
60×60×25mm	B/S	5/12/24	7.0~13.2	0.10~0.36	1.20~4.32	3100~6800	0.40~0.99	14.10~34.80	2.50~13.00	0.10~0.51	26.0~46.5
60×60×38mm	B/S	5/12/24/48	7.0~13.2	0.60~1.80	7.20~21.60	8000~12000	1.22~1.90	43.10~67.30	22.90~52.60	0.90~2.07	51.0~61.8
70×70×10mm	B/S	5/12/24	7.0~13.2	0.09~0.28	1.08~3.36	2800~4300	0.60~0.99	21.19~35.00	2.01~4.97	0.08~0.20	27.0~38.5
70×70×15mm	B/S	5/12/24	7.0~13.2	0.10~0.25	1.20~3.00	2800~4300	0.60~0.95	21.10~33.50	2.30~5.50	0.09~0.22	27.0~39.0
70×70×20mm	B/S	5/12/24	7.0~13.2	0.11~0.35	1.32~4.20	3200~5000	0.83~1.33	29.16~46.86	2.99~7.24	0.12~0.29	32.0~44.3
70×70×25mm	B/S	5/12/24	7.0~13.2	0.07~0.16	0.84~1.92	3000~5500	0.85~1.55	30.00~54.80	3.90~12.80	0.15~0.50	27.0~45.0
80×80×10mm	B/S	5/12/24	7.0~13.2	0.15~0.25	1.80~3.00	2500~3300	0.51~0.67	18.11~23.81	1.29~2.40	0.05~0.08	26.4~32.4
80×80×15mm	B/S	5/12/24	7.0~13.2	0.06~0.30	0.72~3.60	2400~4500	0.65~1.35	23.10~47.60	1.50~5.50	0.06~0.22	28.0~43.0
80×80×20mm	B/S	5/12/24	7.0~13.2	0.09~0.26	1.08~3.12	2400~4300	0.78~1.45	27.40~51.20	2.20~7.20	0.09~0.28	25.0~43.0
80×80×25mm	B/S	5/12/24/48	7.0~13.2	0.65~0.70	7.80~8.40	5000~6000	1.72~2.07	60.80~73.00	10.30~14.80	0.40~0.58	46.0~51.0
80×80×38mm	B/S	5/12/24/48	7.0~13.2	0.40~2.60	4.80~31.20	4200~9000	1.65~3.68	58.20~130.00	10.40~50.90	0.41~2.00	45.0~65.5
92×92×25mm	B/S	5/12/24/48	7.0~13.2	0.09~0.41	1.08~4.92	2100~4200	1.11~2.29	39.20~81.0	2.20~9.20	0.09~0.40	25.0~49.0
92×92×38mm	B/S	5/12/24/48	7.0~13.2	0.55~3.10	6.60~37.20	4400~8000	2.66~4.95	94.11~174.98	14.58~46.03	0.57~1.81	51.2~66.5
120×120×25mm	B/S	5/12/24/48	7.0~13.2	0.36~0.96	4.32~11.52	2500~3400	2.60~3.54	91.90~125.10	5.50~10.20	0.22~0.40	37.0~45.0
120×120×38mm	B/S	5/12/24/48	7.0~13.2	0.20~1.41	4.80~16.92	2600~5200	3.25~7.05	114.70~238.40	10.40~23.80	0.41~0.94	41.0~54.0
140×140×25mm	B/S	5/12/24/48	7.0~13.2	0.16~0.38	1.92~4.56	1200~2000	1.78~2.78	63.0~98.4	1.20~2.80	0.05~0.11	25.0~38.0
150×150×50mm	B/S	12/24/48	28.0~56.0	0.90~1.50	43.20~72.00	3500~4400	7.79~7.79	275~332	22.5~34.2	0.89~1.35	57.0~63.5
172×150×51mm	B/S	12/24/48	28.0~56.0	0.90~1.50	43.20~72.00	3500~4400	7.79~7.79	275~332	22.5~34.2	0.89~1.35	57.0~63.5
200×200×60mm	B	12/24/48	28.0~56.0	0.40~1.10	19.20~52.80	2000~2800	12.04~16.86	425~595	46.40~65.00	1.82~2.55	46.5~74.4
254×89mm	B	12/24/48	28.0~56.0	0.20~4.8	9~168	1000~3500	8.70~30.00	308~718	12.50~39.5	0.49~1.56	51.2~78.9

280×280×89mm	B	12/24/48	28.0~56.0	57.6	124.8	2750	32	1130	22.44	0.88	70
--------------	---	----------	-----------	------	-------	------	----	------	-------	------	----

特别说明：

- 1、电压：电压可做常用与非常用两种，常用电压分别是（5伏、12伏、24伏、48伏），非常用电压是（3伏、15伏、60伏、110伏、220伏）等
- 2、可特殊制造如：防水、防潮、PWM调速、RD与FG信号反馈、温控、自动保护等。
- 3、新品开发：我司可配合用户开发与之匹配的风机，如：来样定制、来样开发等
- 4、如果以上没有您要的规格及参数，请与我们销售代表联系并索取，或进入我司官方网站索取。

