

30 cooling fan

× 30 × 07mm



General Specifications

- Motor : 6 Poles brushless DC motor
- Frame & Impeller: Plastic (UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

Major Characteristic Parameters

品牌	轴承	电压	启动电压	电流	功率	转速	风量	静压	噪音		
型号	B/S	V	V	A	W	RPM	m ³ /min	CFM	mm-H ₂ O	In-H ₂ O	dba
SP30S05L-07DL	S	5	4.5~5.5	0.13	0.65	5000	0.05	0.79	1.30	0.05	22.5
SP30S12L-07DL	S	12	7.0~13.2	0.04	0.48	5000	0.05	0.79	1.30	0.05	22.5
SP30S05M-07DL	S	5	4.5~5.5	0.17	0.85	8000	0.08	2.68	1.90	0.08	28.6
SP30S12M-07DL	S	12	7.0~13.2	0.06	0.72	8000	0.08	2.68	1.90	0.08	28.6
SP30S05H-07DL	S	5	4.5~5.5	0.25	1.25	11000	0.11	3.92	2.90	0.11	32.6
SP30S12H-07DL	S	12	7.0~13.2	0.10	1.20	11000	0.11	3.92	2.90	0.11	32.6
SP30S05U-07DL	S	5	4.5~5.5	0.32	1.60	13000	0.12	4.25	3.58	0.14	36.80
SP30S12U-07DL	S	12	7.0~13.2	0.12	1.44	13000	0.12	4.25	3.58	0.14	36.80

*Bearing system B: Two Ball Bearing S: Sleeve Bearing

