

□ 50 cooling fan ×50×10mm



General Specifications

- Motor : 6 Poles brushless DC motor
- Frame & Impeller: Plastic (UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

Major Characteristic Parameters

品牌	轴承	电压	启动电压	电流	功率	转速	风量	静压	噪音		
型号	B/S	V	V	A	W	RPM	m ³ /min	CFM	mm-H ₂ O	In-H ₂ O	dba
SP50B05L-10DL	B / S	5	4.0~6.0	0.08	0.40	3500	0.19	6.70	1.40	0.05	18.0
SP50B12L-10DL	B / S	12	6.0~13.8	0.05	0.60	3500	0.19	6.70	1.40	0.05	18.0
SP50B05M-10DL	B / S	5	4.0~6.0	0.12	0.60	4500	0.24	8.60	2.20	0.09	25.0
SP50B12M-10DL	B / S	12	6.0~13.8	0.07	0.84	4500	0.24	8.60	2.20	0.09	25.0
SP50B05H-10DL	B / S	5	4.0~6.0	0.16	0.80	5500	0.30	10.50	3.50	0.14	30.0
SP50B12H-10DL	B / S	12	6.0~13.8	0.08	0.96	5500	0.30	10.50	3.50	0.14	30.0
SP50B05U-10DL	B / S	5	4.0~6.0	0.20	1.00	6500	0.36	12.70	4.50	0.18	35.0
SP50B12U-10DL	B / S	12	6.0~13.8	0.10	1.20	6500	0.36	12.70	4.50	0.18	35.0

* Bearing system B: Two Ball Bearing S: Sleeve Bearing

