

□ 50 cooling fan ×50×15mm



■ General Specifications

- Motor : 6 Poles brushless DC motor
- Frame & Impeller: Plastic (UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

■ Major Characteristic Parameters

品牌	轴承	电压	启动电压	电流	功率	转速	风量	静压	噪音		
型号	B/S	V	V	A	W	RPM	m3/min	CFM	mm-H ₂ O	In-H ₂ O	dba
SP50B12L-15DL	B / S	12	7.0~13.2	0.10	1.20	4000	0.28	10.00	2.80	0.11	24.0
SP50B24L-15DL	B / S	24	14.0~26.4	0.07	1.68	4000	0.28	10.00	2.80	0.11	24.0
SP50B12M-15DL	B / S	12	7.0~13.2	0.13	1.56	4800	0.34	11.80	3.80	0.15	28.0
SP50B24M-15DL	B / S	24	14.0~26.4	0.08	1.92	4800	0.34	11.80	3.80	0.15	28.0
SP50B12H-15DL	B / S	12	7.0~13.2	0.15	1.80	5600	0.39	13.80	5.10	0.20	32.0
SP50B24H-15DL	B / S	24	14.0~26.4	0.10	2.40	5600	0.39	13.80	5.10	0.20	32.0
SP50B12U-15DL	B / S	12	7.0~13.2	0.21	2.52	6400	0.45	15.80	7.00	0.27	36.0
SP50B24U-15DL	B / S	24	14.0~26.4	0.12	2.88	6400	0.45	15.80	7.00	0.27	36.0

* Bearing system B: Two Ball Bearing S: Sleeve Bearing

