

□ 60 cooling fan ×60×10mm



■ General Specifications

- Motor : 6 Poles brushless DC motor
- Frame & Impeller: Plastic (UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

■ Major Characteristic Parameters

品牌	轴承	电压	启动电压	电流	功率	转速	风量	静压	噪音		
型号	B/S	V	V	A	W	RPM	m3/min	CFM	mm-H ₂ O	In-H ₂ O	dba
SP60B12L-10DL	B / S	12	7.0~13.2	0.13	1.56	3500	0.49	17.4	2.10	0.08	28.0
SP60B24L-10DL	B / S	24	14.0~26.4	0.08	1.92	3500	0.49	17.4	2.10	0.08	28.0
SP60B12M-10DL	B / S	12	7.0~13.2	0.17	2.04	4200	0.59	20.8	3.00	0.12	33.0
SP60B24M-10DL	B / S	24	14.0~26.4	0.11	2.64	4200	0.59	20.8	3.00	0.12	33.0
SP60B12H-10DL	B / S	12	7.0~13.2	0.24	2.88	4900	0.69	24.3	4.10	0.16	37.0
SP60B24H-10DL	B / S	24	14.0~26.4	0.15	3.60	4900	0.69	24.3	4.10	0.16	37.0

* Bearing system B: Two Ball Bearing S: Sleeve Bearing

