

□ 70 cooling fan × 70 × 10mm



■ General Specifications

- Motor : 6 Poles brushless DC motor
- Frame & Impeller: Plastic (UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

■ Major Characteristic Parameters

品牌	轴承	电压	启动电压	电流	功率	转速	风量	静压	噪音		
型号	B/S	V	V	A	W	RPM	m ³ /min	CFM	mm-H ₂ O	in-H ₂ O	dba
SP70B12L-10DL	B / S	12	7.0~13.2	0.09	1.08	2800	0.60	21.19	2.01	0.08	27.0
SP70B24L-10DL	B / S	24	14.0~26.4	0.07	1.68	2800	0.60	21.19	2.01	0.08	27.0
SP70B12M-10DL	B / S	12	7.0~13.2	0.16	1.92	3300	0.75	26.49	2.89	0.11	31.5
SP70B24M-10DL	B / S	24	14.0~26.4	0.09	2.16	3300	0.75	26.49	2.89	0.11	31.5
SP70B12H-10DL	B / S	12	7.0~13.2	0.22	2.64	3800	0.88	31.01	3.75	0.15	35.0
SP70B24H-10DL	B / S	24	14.0~26.4	0.14	3.36	3800	0.88	31.01	3.75	0.15	35.0
SP70B12U-10DL	B / S	12	7.0~13.2	0.28	3.36	4300	0.99	35.00	4.97	0.20	38.5
SP70B24U-10DL	B / S	24	14.0~26.4	0.17	4.08	4300	0.99	35.00	4.97	0.20	38.5

* Bearing system B: Two Ball Bearing S: Sleeve Bearing

