

80 cooling fan ×80×20mm



General Specifications

- Motor : 6 Poles brushless DC motor
- Frame & Impeller: Plastic (UL 94V-0)
- Storage temperature : -40° to +75°
- Operating temperature : -10° to +70°

Major Characteristic Parameters

品牌	轴承	电压	启动电压	电流	功率	转速	风量	静压	噪音		
型号	B/S	V	V	A	W	RPM	m ³ /min	CFM	mm-H ₂ O	In-H ₂ O	dba
SP80B12J-20DL	B / S	12	7.0~13.2	0.09	1.08	2400	0.78	27.4	2.2	0.09	25.0
SP80B24J-20DL	B / S	24	14.0~26.4	0.05	1.20	2400	0.78	27.4	2.2	0.09	25.0
SP80B12L-20DL	B / S	12	7.0~13.2	0.10	1.20	2700	0.88	31.2	2.8	0.11	29.0
SP80B24L-20DL	B / S	24	14.0~26.4	0.07	1.68	2700	0.88	31.2	2.8	0.11	29.0
SP80B12M-20DL	B / S	12	7.0~13.2	0.12	1.44	3100	1.04	36.9	3.7	0.15	34.0
SP80B24M-20DL	B / S	24	14.0~26.4	0.09	2.16	3100	1.04	36.9	3.7	0.15	34.0
SP80B12H-20DL	B / S	12	7.0~13.2	0.14	1.68	3400	1.15	40.5	4.5	0.18	36.0
SP80B24H-20DL	B / S	24	14.0~26.4	0.12	2.88	3400	1.15	40.5	4.5	0.18	36.0
SP80B12U-20DL	B / S	12	7.0~13.2	0.26	3.12	4300	1.45	51.2	7.2	0.28	43.0
SP80B24U-20DL	B / S	24	14.0~26.4	0.16	3.84	4300	1.45	51.2	7.2	0.28	43.0

*Bearing system B: Two Ball Bearing S: Sleeve Bearing

