


SPECIFICATIONS

DISPLAY MODE : STN,YELLOW, GREEN , POSITIVE MODE
 DRIVE CONDITION : 1/64 DUTY , 1/9 BIAS
 VIEWING DIRECTION : 6 O'CLOCK
 OPERATING TEMP : -0°C TO +50°C
 STORAGE TEMP : -10°C TO +60°C
 OPERATING VOLTAGE: 9.0 V
 FRONT POLARIZER : TRANSMISSIVE,ADHESIVE
 BACK POLARIZER : REFLECTIVE,ADHESIVE
 CUSTOMER NO.:
 CONNECTORS : COG (ST7565R)

VIEWING DIRECTION



1	VDD
2	P/S
3	CB6
4	V0
5	V1
6	V2
7	V3
8	V4
9	CAP2N
10	CAP2P
11	CAP1P
12	CAP1N
13	CAP3P
14	VDUT
15	VSS
16	SYMBOL
17	PI17
18	PI6
19	PI5
20	PI4
21	PI3
22	PI2
23	PI1
24	PI0
25	R1D
26	WR
26	A0
27	/RES
28	/CSI

Dwg Title		12848A-34N-28K08	
Dwg No.		2010-01-08	
Scale	Unit	Tol	Dec'te
	mm	±0.2	
Drawn	Checked	Approved	
CHEN			