



# APPROVAL SHEET

MODEL NO: COG-T500MTWH-01P

Approval option:  Specification

Sample

■ **Customer's Confirmation**

|                     |
|---------------------|
| <b>Customer :</b>   |
| <b>Approved by:</b> |
| <b>Date:</b>        |
| <b>Note:</b>        |

■ **Center Confirmed:**

| <b>Approved</b> | <b>Checked by</b> | <b>Made by</b> |
|-----------------|-------------------|----------------|
|                 |                   |                |



## Records of Revision

| DATE      | REF.PAGE<br>PARAGRAPH<br>DRAWING No. | REVISED<br>No. | SUMMARY      | REMARK                         |
|-----------|--------------------------------------|----------------|--------------|--------------------------------|
| 2012-9-13 |                                      | 01             | First issue  |                                |
| 2012-9-18 | P6                                   | 02             | Secend issue | Chang<br>mechanical<br>drawing |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |
|           |                                      |                |              |                                |



## Contents

|    |   |    |
|----|---|----|
| 1  | Introduction-----                               | 4  |
| 2  | General specification-----                      | 5  |
| 3  | Mechanical drawing-----                         | 6  |
| 4  | Absolute maximum ratings-----                   | 7  |
| 5  | Electrical characteristics-----                 | 7  |
| 6  | Optical characteristics -----                   | 11 |
| 7  | Pin Assignment -----                            | 14 |
| 8  | Block diagram -----                             | 15 |
| 9  | Standard Specification for Reliability-----     | 16 |
| 10 | <b>Specification of Quality Assurance</b> ----- | 18 |
| 11 | Packing method-----                             | 26 |
| 12 | TeCenStar LCM Named-----                        | 27 |



## 1. Introduction

### 1.1 Scope of application

This specification applies to the Negative type TFT transmissive dot matrix LCD module ,This LCD module should be designed for mobile phone use.

LCD specification: Dots 800xRGBx480.

As to basic specification of the driver IC, refer to the IC (HX8664B+HX8264D) specification and datasheet.

### 1.2 Structure:

Double display structure:

TFT Module + FPC +BL+TP

FULL 16.7M Color 5.0inch TFT LCD size for main LCD;

One bare chip with gold bump (COG) TECH;

24BIT RGB interface;

### 1.3 TFT features:

Structure: TFT PANNEL+IC+FPC+BL;

Transmissive Type LCD

800 dot-source and 480 dot-gate outputs;

White LED back light;

24BIT RGB interface;

### 1.4 Applications:

Mobile phone

PSP

PDA

GPS


Etc...



## 2. General specification

| ITEM                        | Standard value         | UNIT |
|-----------------------------|------------------------|------|
| LCD Type                    | TFT Transmissive       | ---  |
| Driver element              | a-Si TFT Active matrix |      |
| Number of Dots              | 800*(RGB)*480          | Dots |
| Pixel Arrangement           | RGB Vertical Stripe    |      |
| Active Area                 | 108 *64.8              | mm   |
| Viewing Area (W*H)          | /                      | mm   |
| Viewing Direction           | 12 O'clock             |      |
| Driver IC                   | HX8664B+HX8264D        |      |
| Module Size(W*H*T)          | 120.76x75.85x4.3       | mm   |
| Approx. Weight              | 90                     | g    |
| Back Light                  | White LED              |      |
| System interface            | 24 Bit RGB interface   |      |
| Backlight power consumption | 730mW                  |      |
| Panel power consumption     | ~350mW                 |      |

### 3. Mechanical drawing





## 4. ABSOLUTE MAXIMUM RATINGS

| Parameter                | Symbol    | Min  | Max            | Unit |
|--------------------------|-----------|------|----------------|------|
| Supply voltage for logic | $V_{dd}$  | -0.3 | 4.0            | V    |
| Input voltage for logic  | $V_{IN}$  | -0.5 | $V_{dd} + 0.3$ | V    |
| Supply current (One LED) | $I_{LED}$ |      | 60             | mA   |
| Operating temperature    | $T_{OP}$  | -20  | +70            | °C   |
| Storage temperature      | $T_{ST}$  | -30  | +80            | °C   |

## 5. ELECTRICAL CHARACTERISTICS

### 5.1 Typical Operation Conditions

| Item                  | Symbol    | Min          | Typ | Max          | Unit | Applicable terminal |
|-----------------------|-----------|--------------|-----|--------------|------|---------------------|
| Supply voltage        | $V_{dd}$  | 3.0          | 3.3 | 3.6          | V    | $V_{DD}$            |
| Input voltage         | $V_{IL}$  | -0.3         | -   | $0.2 V_{dd}$ | V    |                     |
|                       | $V_{IH}$  | $0.8 V_{dd}$ | -   | $V_{dd}$     | V    |                     |
| Input leakage current | $I_{LKG}$ | -            | -   | -            | μA   |                     |

### 5.2 Backlight Driving Conditions

| Item                      | Symbol | Values |        |        | Unit | Remark |
|---------------------------|--------|--------|--------|--------|------|--------|
|                           |        | Min.   | Typ.   | Max.   |      |        |
| Voltage for LED backlight | $V_L$  | (17.4) | (18.3) | (19.6) | V    | Note 1 |
| Current for LED backlight | $I_L$  | (30)   | (40)   | (50)   | mA   |        |
| LED life time             | -      | 20,000 | -      | -      | Hr   | Note 2 |

Note 1: The LED Supply Voltage is defined by the number of LED at  $T_a=25^{\circ}\text{C}$  and  $I_L=40\text{mA}$ .

Note 2: The “LED life time” is defined as the module brightness decrease to 50% original brightness at  $T_a=25^{\circ}\text{C}$  and  $I_L=40\text{mA}$ . The LED lifetime could be decreased if operating  $I_L$  is larger than 50mA.



### 5.3. Timing Characteristics

#### 5.3.1. AC Electrical Characteristics

| Item                                | Symbol           | Values |      |      | Unit | Remark                            |
|-------------------------------------|------------------|--------|------|------|------|-----------------------------------|
|                                     |                  | Min.   | Typ. | Max. |      |                                   |
| HS setup time                       | T <sub>hst</sub> | 8      | -    | -    | ns   |                                   |
| HS hold time                        | T <sub>hhd</sub> | 8      | -    | -    | ns   |                                   |
| VS setup time                       | T <sub>vst</sub> | 8      | -    | -    | ns   |                                   |
| VS hold time                        | T <sub>vhd</sub> | 8      | -    | -    | ns   |                                   |
| Data setup time                     | T <sub>dsu</sub> | 8      | -    | -    | ns   |                                   |
| Data hold time                      | T <sub>dhd</sub> | 8      | -    | -    | ns   |                                   |
| DE setup time                       | T <sub>esu</sub> | 8      | -    | -    | ns   |                                   |
| DE hold time                        | T <sub>ehd</sub> | 8      | -    | -    | ns   |                                   |
| DV <sub>DD</sub> Power On Slew rate | T <sub>POR</sub> | -      | -    | 20   | ms   | From 0 to 90%<br>DV <sub>DD</sub> |
| RESET pulse width                   | T <sub>Rst</sub> | 10     | -    | -    | ms   |                                   |
| DCLK cycle time                     | T <sub>coh</sub> | 20     | -    | -    | ns   |                                   |
| DCLK pulse duty                     | T <sub>cwh</sub> | 40     | 50   | 60   | %    |                                   |



### 5.3.2. Data Input Format




Figure 3. 1 Horizontal input timing diagram.




Figure 3. 2 Vertical input timing diagram.



5.3.3. Timing


| Item                    | Symbol | Values |      |      | Unit | Remark |
|-------------------------|--------|--------|------|------|------|--------|
|                         |        | Min.   | Typ. | Max. |      |        |
| Horizontal Display Area | thd    | -      | 800  | -    | DCLK |        |
| DCLK Frequency          | fcclk  |        | 30   | 50   | MHz  |        |
| One Horizontal Line     | th     | 889    | 928  | 1143 | DCLK |        |
| HS pulse width          | thpw   | 1      | 48-  | 255  | DCLK |        |
| HS Blanking             | thb    |        | 88   |      | DCLK |        |
| HS Front Porch          | thfp   | 1      | 40   | 255  | DCLK |        |

| Item                  | Symbol | Values |      |      | Unit | Remark |
|-----------------------|--------|--------|------|------|------|--------|
|                       |        | Min.   | Typ. | Max. |      |        |
| Vertical Display Area | tvd    | -      | 480  | -    | TH   |        |
| VS period time        | tv     | 513    | 525  | 767  | TH   |        |
| VS pulse width        | tvpw   | 3      | 3    | 255  | TH   |        |
| VS Blanking           | tvb    |        | 32   |      | TH   |        |
| VS Front Porch        | tvfp   | 1      | 13   | 255  | TH   |        |

## 6. OPTICAL CHARACTERISTICS

| ITEM                 | SYMBOL         | CONDITIONS           | SPECIFICATIONS |       |       | UNIT              | NOTE  |  |
|----------------------|----------------|----------------------|----------------|-------|-------|-------------------|---|--|
|                      |                |                      | MIN.           | TYP.  | MAX   |                   |   |  |
| Brightness           | B              | Viewing normal angle | 180            | 220   | --    | Cd/m <sup>2</sup> | All left side data are based on TIANMA's product reference only |  |
| Contrast Ratio       | CR             |                      | -              | 500   | --    | --                |   |  |
| Response Time        | Tr+Tf          |                      | --             | 20    | --    | ms                |   |  |
| CIE Color coordinate | Red            |                      | X <sub>R</sub> | 0.540 | 0.590 | 0.640             |   |  |
|                      |                |                      | Y <sub>R</sub> | 0.300 | 0.350 | 0.400             |   |  |
|                      | Green          |                      | X <sub>G</sub> | 0.298 | 0.348 | 0.398             |   |  |
|                      |                |                      | Y <sub>G</sub> | 0.520 | 0.570 | 0.620             |   |  |
|                      | Blue           |                      | X <sub>B</sub> | 0.095 | 0.145 | 0.195             |   |  |
|                      |                |                      | Y <sub>B</sub> | 0.060 | 0.110 | 0.160             |   |  |
| White                | X <sub>w</sub> |                      | 0.260          | 0.310 | 0.360 |                   |   |  |
|                      | Y <sub>w</sub> | 0.280                | 0.330          | 0.380 |       |                   |   |  |
| Viewing Angle        | Hor.           | $\theta_{x+}$        | 60             | 70    | --    | Deg.              |   |  |
|                      |                | $\theta_{x-}$        | 60             | 70    | --    |                   |   |  |
|                      | Ver.           | $\theta_{y+}$        | 40             | 50    | --    |                   |   |  |
|                      |                | $\theta_{y-}$        | 60             | 70    | --    |                   |   |  |
| Uniformity           | Un             |                      | 75             | 80    |       | %                 |   |  |


Note 1 : Definition of Viewing Angle  $\theta_x$  and  $\theta_y$  :



**Note 2: Definition of contrast ratio CR:**


$$CR = \frac{\text{Brightness of non-selected dots (white)}}{\text{Brightness of selected dots (black)}}$$

**Note 3: Definition of response time ( $T_R$ ,  $T_F$ )**




**: The brightness test equipment setup**

20mA Field=2° (As measuring "black" image, field=2° is the best testing condition)



Note 4 :






## 7. Interface Pin Function

| Pin No | Symbol | Function   |
|--------|--------|--|
| 1      | VLED-  | BACK LIGHT POWER GROUND  |
| 2      | VLED+  | BACK LIGHT POWER SUPPLY  |
| 3      | GND    | POWER GROUND   |
| 4      | VDD    | POWER SUPPLY   |
| 5-12   | R0-R7  | RED DATA   |
| 13-20  | G0-G7  | GREEN DATA   |
| 21-28  | B0-B7  | BLUE DATA  |
| 29     | GND    | POWER GROUND   |
| 30     | CLKIN  | In external interface mode, served as a dot clock signal.  |
| 31     | STBYB  | standby mode control pin   |
| 32     | HSD    | In external interface mode, served as a horizontal synchronized signal input                         |
| 33     | VSD    | In external interface mode, served as a vertical synchronize signal input                            |
| 34     | DEN    | In external interface mode, polarity of ENABLE signal is synchronized with valid graphic data input. |
| 35     | NC     | NC   |
| 36     | GND    | POWER GROUND   |
| 37     | XR     | TOUCH PANEL INTERFACE  |
| 38     | YD     |  |
| 39     | XL     |  |
| 40     | YU     |  |

NOTE:For digital RGB input data format, both SYNC mode and DE+SYNC mode are supported. If ENB signal is fixed low. SYNC mode is used. Otherwise, DEN+SYNC is used

## 8. BLOCK DIAGRAM





## 9. Standard Specification for Reliability

### 9-1. Standard Specifications for Reliability of LCD Module

| No | Item                        | Description   |
|----|-----------------------------|---|
| 01 | High temperature operation  | The sample should be allowed to stand at 70°C for 120 hours under driving condition and then returning it to normal temperature condition, and allowing it stand for 2 hours.                       |
| 02 | Low temperature operation   | The sample should be allowed to stand at -20°C for 120 hours under driving condition and then returning it to normal temperature condition, and allowing it stand for 2 hours.                      |
| 03 | High temperature storage    | The sample should be allowed to stand at 80°C for 240 hours under no-load condition, and then returning it to normal temperature condition, and allowing it stand for 2 hours.                      |
| 04 | Low temperature storage     | The sample should be allowed to stand at -30°C for 240 hours under no-load condition, then returning it to normal temperature condition, and allowing it stand for 2 hours.                         |
| 05 | Moisture storage            | The sample should be allowed to stand at 60°C,90%RH MAX for 240 hours under no-load condition, then taking it out and drying it at normal temperature for 2 hours.                                  |
| 06 | Thermal shock storage       | The sample should be allowed to stand the following 10 cycles :<br>-30°C for 30 minutes → normal temperature for 5 minutes → +80°C for 30 minutes → normal temperature for 5 minutes, as one cycle. |
| 07 | Packing vibration           | Frequency range : 10Hz ~ 55Hz<br>Amplitude of vibration : 1.5mm Sweep time: 12 min<br>X,Y,Z 2 hours for each direction.   |
| 08 | Packing drop test           | According to ASTM-D-5327.   |
| 09 | Electrical Static Discharge | Air: ±4KV 150pF/330Ω 5 times  |
|    |                             | Contact: ±2KV 150pF/330Ω 5 time   |

\*Sample size for each test item is 3~5pcs





9 - 2. Testing Conditions and Inspection Criteria

For the final test the testing sample must be stored at room temperature for 24 hours, after the tests listed in Table 12.2, Standard specifications for Reliability have been executed in order to ensure stability.

| No | Item                | Test Model             | In section Criteria  |
|----|---------------------|------------------------|--|
| 01 | Current Consumption | Refer To Specification | The current consumption should conform to the product specification.   |
| 02 | Contrast            | Refer To Specification | After the tests have been executed, the contrast must be larger than half of its initial value prior to the tests. |
| 03 | Appearance          | Visual inspection      | Defect free.   |

9- 3. MTBF

|      |   |
|------|---|
| MTBF | Functions, performance, appearance, etc. shall be free from remarkable deterioration within 50,000 hours under ordinary operating and storage conditions room temperature (25±5°C), normal humidity (50±10% RH), and in area not exposed to direct sun light. |
|------|---|



## 10. Specification of Quality Assurance:

### 10-1. Purpose

This standard for Quality Assurance should affirm the quality of LCD module products to supply to purchaser by TeCenStar

### 10-2. Standard for Quality Test

#### a. Inspection:

Before delivering, the supplier should take the following tests, and affirm the quality of product.

#### b. Electro-Optical Characteristics:

According to the individual specification to test the product.

#### c. Test of Appearance Characteristics:

According to the individual specification to test the product.

#### d. Test of Reliability Characteristics:

According to the definition of reliability on the specification for testing products.

#### e. Delivery Test:

Before delivering, the supplier should take the delivery test.

(i) Test method: According to MIL-STD105E.General Inspection Level II take a single time.

(ii) The defects classify of AQL as following:

Major defect: AQL = 0.65

Minor defect: AQL = 2.5

Total defects: AQL = 2.5

### 10-3. Non-conforming Analysis & Deal With Manners

#### a. Non-conforming Analysis:

(i) Purchaser should supply the detail data of non-conforming sample and the non-conforming.

(ii) After accepting the detail data from purchaser, the analysis of non-conforming should be finished in two weeks.

(iii) If supplier can not finish analysis on time, must announce purchaser before 3 days.

#### b. Disposition of non-conforming:

(i) If find any product defect of supplier during assembly time, supplier must change the good product for every defect after recognition.

(ii) Both supplier and customer should analyze the reason and discuss the disposition of non-conforming when the reason of nonconforming is not sure.

### 10-4. Agreement items

Both sides should discuss together when the following problems happen.

a. There is any problem of standard of quality assurance, and both sides should think that must be modified.


b. There is any argument item which does not record in the standard of quality assurance.

c. Any other special problem.


10-5. Standard of The Product Appearance Test

a. Manner of appearance test:

- (i) The test must be under 20W × 2 or 40W fluorescent light, and the distance of view must be at 30±5cm.
- (ii) When test the model of transmissive product must add the reflective plate.
- (iii) The test direction is base on around 10° of vertical line.
- (iii) Temperature: 25±5°C Humidity: 60±10%RH



(iv) Definition of area:



A. Area: Viewing area.

B. Area: Out of viewing area.  
(Outside viewing area)



b. Basic principle:



- (i) It will accord to the AQL when the standard can not be described.
- (ii) The sample of the lowest acceptable quality level must be discussed by both supplier and customer when any dispute happened.
- (iii) Must add new item on time when it is necessary.




c. Standard of inspection: (Unit: mm)



10-6. Inspection specification



| NO                      | Item  | Criterion   | AQL      |                 |                  |                 |                         |   |                         |   |                         |   |               |   |             |           |                 |     |               |                 |              |                      |   |              |                      |     |            |           |     |
|-------------------------|---|---|----------|-----------------|------------------|-----------------|-------------------------|---|-------------------------|---|-------------------------|---|---------------|---|-------------|-----------|-----------------|-----|---------------|-----------------|--------------|----------------------|---|--------------|----------------------|-----|------------|-----------|-----|
| 01                      | Electrical Testing  | 1.1 Missing vertical, horizontal segment, segment contrast defect.<br>1.2 Missing character, dot or icon.<br>1.3 Display malfunction.<br>1.4 No function or no display.<br>1.5 Current consumption exceeds product specifications.<br>1.6 LCD viewing angle defect.<br>1.7 Mixed product types.<br>1.8 Flicker  | 0.65     |                 |                  |                 |                         |   |                         |   |                         |   |               |   |             |           |                 |     |               |                 |              |                      |   |              |                      |     |            |           |     |
| 02                      | Black or White spots or Bright spots or Color spots on LCD (Display only)   | 2.1 White and black or color spots on display $\leq 0.25\text{mm}$ , no more than Five spots.<br>2.2 Densely spaced: No more than three spots within 3mm.   | 2.5      |                 |                  |                 |                         |   |                         |   |                         |   |               |   |             |           |                 |     |               |                 |              |                      |   |              |                      |     |            |           |     |
| 03                      | LCD and Touch Panel black spots, white spots, contamination (non – display) | <p>3.1 Round type: As following drawing<br/> <math>\Phi = (X+Y) / 2</math></p>  <table border="1" data-bbox="753 976 1286 1187"> <thead> <tr> <th>Size(mm)</th> <th>Acceptable Q'ty</th> </tr> </thead> <tbody> <tr> <td><math>\Phi \leq 0.10</math></td> <td>Accept no dense</td> </tr> <tr> <td><math>0.10 &lt; \Phi \leq 0.20</math></td> <td>2</td> </tr> <tr> <td><math>0.20 &lt; \Phi \leq 0.25</math></td> <td>2</td> </tr> <tr> <td><math>0.25 &lt; \Phi \leq 0.30</math></td> <td>1</td> </tr> <tr> <td><math>0.30 &lt; \Phi</math></td> <td>0</td> </tr> </tbody> </table> <p>* Densely spaced: No more than two spots within 3mm.</p> <p>3.2 Line type: (As following drawing)</p>  <table border="1" data-bbox="655 1303 1286 1507"> <thead> <tr> <th>Length(m m)</th> <th>Width(mm)</th> <th>Acceptable Q'ty</th> </tr> </thead> <tbody> <tr> <td>---</td> <td><math>W \leq 0.02</math></td> <td>Accept no dense</td> </tr> <tr> <td><math>L \leq 3.0</math></td> <td><math>0.02 &lt; W \leq 0.05</math></td> <td rowspan="2">2</td> </tr> <tr> <td><math>L \leq 2.5</math></td> <td><math>0.03 &lt; W \leq 0.08</math></td> </tr> <tr> <td>---</td> <td><math>0.08 &lt; W</math></td> <td>Rejection</td> </tr> </tbody> </table> <p>* Densely spaced: No more than two lines within 3mm.</p> | Size(mm) | Acceptable Q'ty | $\Phi \leq 0.10$ | Accept no dense | $0.10 < \Phi \leq 0.20$ | 2 | $0.20 < \Phi \leq 0.25$ | 2 | $0.25 < \Phi \leq 0.30$ | 1 | $0.30 < \Phi$ | 0 | Length(m m) | Width(mm) | Acceptable Q'ty | --- | $W \leq 0.02$ | Accept no dense | $L \leq 3.0$ | $0.02 < W \leq 0.05$ | 2 | $L \leq 2.5$ | $0.03 < W \leq 0.08$ | --- | $0.08 < W$ | Rejection | 2.5 |
| Size(mm)                | Acceptable Q'ty   |   |          |                 |                  |                 |                         |   |                         |   |                         |   |               |   |             |           |                 |     |               |                 |              |                      |   |              |                      |     |            |           |     |
| $\Phi \leq 0.10$        | Accept no dense   |   |          |                 |                  |                 |                         |   |                         |   |                         |   |               |   |             |           |                 |     |               |                 |              |                      |   |              |                      |     |            |           |     |
| $0.10 < \Phi \leq 0.20$ | 2   |   |          |                 |                  |                 |                         |   |                         |   |                         |   |               |   |             |           |                 |     |               |                 |              |                      |   |              |                      |     |            |           |     |
| $0.20 < \Phi \leq 0.25$ | 2   |   |          |                 |                  |                 |                         |   |                         |   |                         |   |               |   |             |           |                 |     |               |                 |              |                      |   |              |                      |     |            |           |     |
| $0.25 < \Phi \leq 0.30$ | 1   |   |          |                 |                  |                 |                         |   |                         |   |                         |   |               |   |             |           |                 |     |               |                 |              |                      |   |              |                      |     |            |           |     |
| $0.30 < \Phi$           | 0   |   |          |                 |                  |                 |                         |   |                         |   |                         |   |               |   |             |           |                 |     |               |                 |              |                      |   |              |                      |     |            |           |     |
| Length(m m)             | Width(mm)   | Acceptable Q'ty   |          |                 |                  |                 |                         |   |                         |   |                         |   |               |   |             |           |                 |     |               |                 |              |                      |   |              |                      |     |            |           |     |
| ---                     | $W \leq 0.02$   | Accept no dense   |          |                 |                  |                 |                         |   |                         |   |                         |   |               |   |             |           |                 |     |               |                 |              |                      |   |              |                      |     |            |           |     |
| $L \leq 3.0$            | $0.02 < W \leq 0.05$  | 2   |          |                 |                  |                 |                         |   |                         |   |                         |   |               |   |             |           |                 |     |               |                 |              |                      |   |              |                      |     |            |           |     |
| $L \leq 2.5$            | $0.03 < W \leq 0.08$  |   |          |                 |                  |                 |                         |   |                         |   |                         |   |               |   |             |           |                 |     |               |                 |              |                      |   |              |                      |     |            |           |     |
| ---                     | $0.08 < W$  | Rejection   |          |                 |                  |                 |                         |   |                         |   |                         |   |               |   |             |           |                 |     |               |                 |              |                      |   |              |                      |     |            |           |     |

| NO                      | Item                  | Criterion  | AQL               |                 |                  |                 |                         |               |                         |                 |               |                   |               |                |               |                       |               |                    |                 |               |     |
|-------------------------|-----------------------|--|-------------------|-----------------|------------------|-----------------|-------------------------|---------------|-------------------------|-----------------|---------------|-------------------|---------------|----------------|---------------|-----------------------|---------------|--------------------|-----------------|---------------|-----|
| 04                      | Polarizer bubbles     | If bubbles are visible, judge using black spot specifications, not easy to find, must check in specify direction <table border="1" data-bbox="790 347 1284 548"> <thead> <tr> <th>Size <math>\Phi</math>(mm)</th> <th>Acceptable Q'ty</th> </tr> </thead> <tbody> <tr> <td><math>\Phi \leq 0.20</math></td> <td>Accept no dense</td> </tr> <tr> <td><math>0.20 &lt; \Phi \leq 0.50</math></td> <td>3</td> </tr> <tr> <td><math>0.50 &lt; \Phi \leq 1.00</math></td> <td>2</td> </tr> <tr> <td><math>1.00 &lt; \Phi</math></td> <td>0</td> </tr> <tr> <td>Total Q'ty</td> <td>3</td> </tr> </tbody> </table>  | Size $\Phi$ (mm)  | Acceptable Q'ty | $\Phi \leq 0.20$ | Accept no dense | $0.20 < \Phi \leq 0.50$ | 3             | $0.50 < \Phi \leq 1.00$ | 2               | $1.00 < \Phi$ | 0                 | Total Q'ty    | 3              | 2.5           |                       |               |                    |                 |               |     |
| Size $\Phi$ (mm)        | Acceptable Q'ty       |  |                   |                 |                  |                 |                         |               |                         |                 |               |                   |               |                |               |                       |               |                    |                 |               |     |
| $\Phi \leq 0.20$        | Accept no dense       |  |                   |                 |                  |                 |                         |               |                         |                 |               |                   |               |                |               |                       |               |                    |                 |               |     |
| $0.20 < \Phi \leq 0.50$ | 3                     |  |                   |                 |                  |                 |                         |               |                         |                 |               |                   |               |                |               |                       |               |                    |                 |               |     |
| $0.50 < \Phi \leq 1.00$ | 2                     |  |                   |                 |                  |                 |                         |               |                         |                 |               |                   |               |                |               |                       |               |                    |                 |               |     |
| $1.00 < \Phi$           | 0                     |  |                   |                 |                  |                 |                         |               |                         |                 |               |                   |               |                |               |                       |               |                    |                 |               |     |
| Total Q'ty              | 3                     |  |                   |                 |                  |                 |                         |               |                         |                 |               |                   |               |                |               |                       |               |                    |                 |               |     |
| 05                      | Scratches             | Follow NO.3 -2 Line Type.  |                   |                 |                  |                 |                         |               |                         |                 |               |                   |               |                |               |                       |               |                    |                 |               |     |
| 06                      | Chipped glass         | Symbols:<br>x: Chip length y: Chip width z: Chip thickness<br>k: Seal width t: Glass thickness a: LCD side length<br>L: Electrode pad length<br>6.1 General glass chip:<br>6.1.1 Chip on panel surface and crack between panels:<br> <table border="1" data-bbox="335 985 1157 1086"> <thead> <tr> <th>z: Chip thickness</th> <th>y: Chip width</th> <th>x: Chip length</th> </tr> </thead> <tbody> <tr> <td><math>Z \leq 1/2t</math></td> <td>Not over viewing area</td> <td><math>x \leq 1/8a</math></td> </tr> <tr> <td><math>1/2t &lt; z \leq 2t</math></td> <td>Not exceed 1/3k</td> <td><math>x \leq 1/8a</math></td> </tr> </tbody> </table> <ul style="list-style-type: none"> <li>⊙ Unit: mm</li> <li>⊙ If there are 2 or more chips, x is the total length of each chip</li> </ul> 6.1.2 Corner crack:<br> <table border="1" data-bbox="335 1444 1157 1556"> <thead> <tr> <th>z: Chip thickness</th> <th>y: Chip width</th> <th>x: Chip length</th> </tr> </thead> <tbody> <tr> <td><math>Z \leq 1/2t</math></td> <td>Not over viewing area</td> <td><math>x \leq 1/8a</math></td> </tr> <tr> <td><math>1/2t &lt; z \leq 2t</math></td> <td>Not exceed 1/3k</td> <td><math>x \leq 1/8a</math></td> </tr> </tbody> </table> <ul style="list-style-type: none"> <li>⊙ Unit: mm</li> <li>⊙ If there are 2 or more chips, x is the total length of each chip</li> </ul> | z: Chip thickness | y: Chip width   | x: Chip length   | $Z \leq 1/2t$   | Not over viewing area   | $x \leq 1/8a$ | $1/2t < z \leq 2t$      | Not exceed 1/3k | $x \leq 1/8a$ | z: Chip thickness | y: Chip width | x: Chip length | $Z \leq 1/2t$ | Not over viewing area | $x \leq 1/8a$ | $1/2t < z \leq 2t$ | Not exceed 1/3k | $x \leq 1/8a$ | 2.5 |
| z: Chip thickness       | y: Chip width         | x: Chip length   |                   |                 |                  |                 |                         |               |                         |                 |               |                   |               |                |               |                       |               |                    |                 |               |     |
| $Z \leq 1/2t$           | Not over viewing area | $x \leq 1/8a$  |                   |                 |                  |                 |                         |               |                         |                 |               |                   |               |                |               |                       |               |                    |                 |               |     |
| $1/2t < z \leq 2t$      | Not exceed 1/3k       | $x \leq 1/8a$  |                   |                 |                  |                 |                         |               |                         |                 |               |                   |               |                |               |                       |               |                    |                 |               |     |
| z: Chip thickness       | y: Chip width         | x: Chip length   |                   |                 |                  |                 |                         |               |                         |                 |               |                   |               |                |               |                       |               |                    |                 |               |     |
| $Z \leq 1/2t$           | Not over viewing area | $x \leq 1/8a$  |                   |                 |                  |                 |                         |               |                         |                 |               |                   |               |                |               |                       |               |                    |                 |               |     |
| $1/2t < z \leq 2t$      | Not exceed 1/3k       | $x \leq 1/8a$  |                   |                 |                  |                 |                         |               |                         |                 |               |                   |               |                |               |                       |               |                    |                 |               |     |

| NO                    | Item           | Criterion   | AQL           |                |                   |                       |               |                |               |                |                   |            |               |                |          |           |               |            |     |
|-----------------------|----------------|---|---------------|----------------|-------------------|-----------------------|---------------|----------------|---------------|----------------|-------------------|------------|---------------|----------------|----------|-----------|---------------|------------|-----|
| 07                    | Glass crack    | <p>Symbols:<br/>           x: Chip length    y: Chip width    z: Chip thickness<br/>           k: Seal width    t: Glass thickness    a: LCD side length<br/>           L: Electrode pad length</p> <p>7.2 Protrusion over terminal:<br/>           7.2.1 Chip on electrode pad:</p>  <table border="1" data-bbox="470 689 1145 835"> <tr> <td>y: Chip width</td> <td>x: Chip length</td> <td>z: Chip thickness</td> </tr> <tr> <td><math>y \leq 0.5\text{mm}</math></td> <td><math>x \leq 1/8a</math></td> <td><math>0 &lt; z \leq t</math></td> </tr> </table> <p>7.2.2 Non-conductive portion:</p>  <table border="1" data-bbox="470 1160 1145 1305"> <tr> <td>y: Chip width</td> <td>x: Chip length</td> <td>z: Chip thickness</td> </tr> <tr> <td><math>y \leq L</math></td> <td><math>x \leq 1/8a</math></td> <td><math>0 &lt; z \leq t</math></td> </tr> </table> <p>⊙ If there chipped area touches the ITO terminal, over 2/3 of the ITO must remain and be inspected according to electrode terminal specifications.<br/>           ⊙ If the product will be heat sealed by the customer, the alignment mark must not be damaged.</p> <p>7.2.3 Substrate protuberance and internal crack</p>  <table border="1" data-bbox="794 1541 1225 1686"> <tr> <td>y: width</td> <td>x: length</td> </tr> <tr> <td><math>y \leq 1/3L</math></td> <td><math>X \leq a</math></td> </tr> </table> | y: Chip width | x: Chip length | z: Chip thickness | $y \leq 0.5\text{mm}$ | $x \leq 1/8a$ | $0 < z \leq t$ | y: Chip width | x: Chip length | z: Chip thickness | $y \leq L$ | $x \leq 1/8a$ | $0 < z \leq t$ | y: width | x: length | $y \leq 1/3L$ | $X \leq a$ | 2.5 |
| y: Chip width         | x: Chip length | z: Chip thickness   |               |                |                   |                       |               |                |               |                |                   |            |               |                |          |           |               |            |     |
| $y \leq 0.5\text{mm}$ | $x \leq 1/8a$  | $0 < z \leq t$  |               |                |                   |                       |               |                |               |                |                   |            |               |                |          |           |               |            |     |
| y: Chip width         | x: Chip length | z: Chip thickness   |               |                |                   |                       |               |                |               |                |                   |            |               |                |          |           |               |            |     |
| $y \leq L$            | $x \leq 1/8a$  | $0 < z \leq t$  |               |                |                   |                       |               |                |               |                |                   |            |               |                |          |           |               |            |     |
| y: width              | x: length      |   |               |                |                   |                       |               |                |               |                |                   |            |               |                |          |           |               |            |     |
| $y \leq 1/3L$         | $X \leq a$     |   |               |                |                   |                       |               |                |               |                |                   |            |               |                |          |           |               |            |     |





| NO | Item               | Criterion  | AQL                                      |
|----|--------------------|--|--|
| 08 | Cracked glass      | The LCD with extensive crack is not acceptable.  | 2.5                                      |
| 09 | Backlight elements | 9.1 Illumination source flickers when lit.<br>9.2 Spots or scratches that appear when lit must be judged. Using LCD spot, lines and contamination standards.<br>9.3 Backlight doesn't light or color is wrong.   | 2.5<br>2.5<br>0.65                       |
| 10 | Bezel              | Bezel must comply with product specifications.   | 2.5                                      |
| 11 | PCB、COB            | 11.1 COB seal may not have pinholes larger than 0.2mm or contamination.<br>11.2 COB seal surface may not have pinholes through to the IC.<br>11.3 The height of the COB should not exceed the height indicated in the assembly diagram.<br>11.4 There may not be more than 2mm of sealant outside the seal area on PCB. And there should be no more than three places.<br>11.5 Parts on PCB must be the same as on the production characteristic chart, There should be no wrong parts, missing parts or excess parts.<br>11.6 The jumper on the PCB should conform to the product characteristic chart. | 2.5<br>2.5<br>2.5<br>2.5<br>0.65<br>0.65 |
| 12 | FPC                | 12.1 FPC terminal damage $\leq$ 1/2 FPC terminal width and can not affect the function , we judge accept.<br>12.2 FPC alignment hole damage $\leq$ 1/2 alignment area and can not affect the function , we judge accept.   | 2.5<br>2.5                               |
| 13 | Soldering          | 13.1 No cold solder joints, missing solder connections, oxidation or icicle.<br>13.2 No short circuits in components on PCB or FPC.  | 2.5<br>0.65                              |

| NO                | Item                                   | Criterion   | AQL               |               |                |            |  |               |                   |               |                |            |  |               |     |
|-------------------|--|---|-------------------|---------------|----------------|------------|--|---------------|-------------------|---------------|----------------|------------|--|---------------|-----|
| 14                | Touch Panel Chipped glass              | <p>Symbols:<br/> x: Chip length y: Chip width z: Chip thickness<br/> k: Seal width t: Touch Panel Total thickness a: LCD side length<br/> L: Electrode pad length</p> <p>14.1 General glass chip:<br/> 14.1.1 Chip on panel surface and crack between panels:</p>  <table border="1" data-bbox="335 828 1157 1041"> <tr> <td>z: Chip thickness</td> <td>y: Chip width</td> <td>x: Chip length</td> </tr> <tr> <td><math>Z \leq t</math></td> <td><math>\leq 1/2 k</math> and not over viewing area</td> <td><math>x \leq 1/8a</math></td> </tr> </table> <p>⊙ Unit: mm<br/> ⊙ If there are 2 or more chips, x is the total length of each chip</p> <p>14.1.2 Corner crack:</p>  <table border="1" data-bbox="335 1355 1157 1568"> <tr> <td>z: Chip thickness</td> <td>y: Chip width</td> <td>x: Chip length</td> </tr> <tr> <td><math>z \leq t</math></td> <td><math>\leq 1/2 k</math> and not over viewing area</td> <td><math>x \leq 1/8a</math></td> </tr> </table> <p>⊙ Unit: mm<br/> ⊙ If there are 2 or more chips, x is the total length of each chip</p> | z: Chip thickness | y: Chip width | x: Chip length | $Z \leq t$ | $\leq 1/2 k$ and not over viewing area | $x \leq 1/8a$ | z: Chip thickness | y: Chip width | x: Chip length | $z \leq t$ | $\leq 1/2 k$ and not over viewing area | $x \leq 1/8a$ | 2.5 |
| z: Chip thickness | y: Chip width                          | x: Chip length  |                   |               |                |            |  |               |                   |               |                |            |  |               |     |
| $Z \leq t$        | $\leq 1/2 k$ and not over viewing area | $x \leq 1/8a$   |                   |               |                |            |  |               |                   |               |                |            |  |               |     |
| z: Chip thickness | y: Chip width                          | x: Chip length  |                   |               |                |            |  |               |                   |               |                |            |  |               |     |
| $z \leq t$        | $\leq 1/2 k$ and not over viewing area | $x \leq 1/8a$   |                   |               |                |            |  |               |                   |               |                |            |  |               |     |






| NO                 | Item  | Criterion   | AQL                          |                 |                 |                 |                    |   |                    |   |           |   |     |
|--------------------|---|---|------------------------------|-----------------|-----------------|-----------------|--------------------|---|--------------------|---|-----------|---|-----|
| 15                 | Touch Panel(Fish eye、dent and bubble on film) | <table border="1" data-bbox="335 443 866 616"> <thead> <tr> <th>SIZE(mm)</th> <th>Acceptable Q'ty</th> </tr> </thead> <tbody> <tr> <td><math>\Phi \leq 0.2</math></td> <td>Accept no dense</td> </tr> <tr> <td><math>0.2 &lt; D \leq 0.4</math></td> <td>5</td> </tr> <tr> <td><math>0.4 &lt; D \leq 0.5</math></td> <td>2</td> </tr> <tr> <td><math>0.5 &lt; D</math></td> <td>0</td> </tr> </tbody> </table>   | SIZE(mm)                     | Acceptable Q'ty | $\Phi \leq 0.2$ | Accept no dense | $0.2 < D \leq 0.4$ | 5 | $0.4 < D \leq 0.5$ | 2 | $0.5 < D$ | 0 | 2.5 |
| SIZE(mm)           | Acceptable Q'ty                               |   |                              |                 |                 |                 |                    |   |                    |   |           |   |     |
| $\Phi \leq 0.2$    | Accept no dense                               |   |                              |                 |                 |                 |                    |   |                    |   |           |   |     |
| $0.2 < D \leq 0.4$ | 5   |   |                              |                 |                 |                 |                    |   |                    |   |           |   |     |
| $0.4 < D \leq 0.5$ | 2   |   |                              |                 |                 |                 |                    |   |                    |   |           |   |     |
| $0.5 < D$          | 0   |   |                              |                 |                 |                 |                    |   |                    |   |           |   |     |
| 16                 | Touch Panel<br>Newton ring                    | Newton ring dimension $\leq 1/2$ touch panel area and not affect font and line distortion( $\leq 2.5\%$ ), it is acceptable.  | 2.5                          |                 |                 |                 |                    |   |                    |   |           |   |     |
| 17                 | Touch Panel<br>Linearity                      | Less than 2.5% is acceptable.   | 2.5                          |                 |                 |                 |                    |   |                    |   |           |   |     |
| 18                 | LCD Ripple                                    | Touch the touch panel , can not see the LCD ripple.<br>Pen: R 1.0mm silicon rubber.<br>Operation Force: 80g   | 2.5                          |                 |                 |                 |                    |   |                    |   |           |   |     |
| 19                 | General appearance                            | 19.1 Pin type must match type in specification sheet.<br>19.2 LCD pin loose or missing pins.<br>19.3 Product packaging must the same as specified on packaging specification sheet.<br>19.4 Product dimension and structure must conform to product specification sheet.  | 0.65<br>0.65<br>0.65<br>0.65 |                 |                 |                 |                    |   |                    |   |           |   |     |

### 11. Packing method

|      |        |           |      |      |                     |              |              |
|------|--------|-----------|------|------|---------------------|--------------|--------------|
| VER. | SYMBOL | AMENDMENT | SIGN | DATE | DRAWN               | TITLE        | DRAWING NO.  |
| 00   |        |           |      |      | MER CHECKED         | MODULE SPEC. | UNIT         |
|      |        |           |      |      | EE CHECKED          |              | mm           |
|      |        |           |      |      | APPROVED            |              | SCALE        |
|      |        |           |      |      | CUSTOMER'S APPROVAL |              | 1            |
|      |        |           |      |      |                     |              | SHEET 1 OF 1 |

$2 \times 20 \times 2 / 80 \text{ pcs / box}$   
 内箱平面积  
 内箱卡板  
 285.000  
 345.000  
 2PCS LCM  
 2PCS LCM  
 2PCS LCM  
 LCM  
 ANTI\_STATIC\_BAG  
 外箱W285\*H345\*100(mm)  
 内装2CASE  
 外箱W315\*H385\*H227(mm)



## 12.TeCenStar LCM Named

COG - (A) (B) (C) (D) (E) (F) – 01 (Example: COG-C147MVHC-01 or COG-T240MZQI-01)

Or

TLM - (A) (B) (C) (D) (E) (F) – 01 (for Module with COG Process)

(A) Type:

|      |      |   |   |
|------|------|---|---|
| TFT  | ---- | T |   |
| CSTN | ---- | C |   |
| OLED | ---- |   | O |
| PLED | ---- |   | P |

(B) Size:

|        |      |     |     |
|--------|------|-----|-----|
| 1.18'' | ---- | 118 |     |
| 2.83'' | ---- |     | 283 |
| 10.4'' | ---- |     | A40 |
| 15''   | ---- |     | F00 |

(C) Mode:

For CSTN/TFT

|                |      |   |  |
|----------------|------|---|--|
| Transflective: | ---- | F |  |
| Transmissive:  | ---- | M |  |

For OLED/PLED

|             |      |   |  |
|-------------|------|---|--|
| Mono:       | ---- | S |  |
| Area Color: | ---- | A |  |
| Color :     | ---- | C |  |
| Grayscale:  | ---- | G |  |

(D) Panel Supplier:

|            |      |   |   |
|------------|------|---|---|
| ALPS       | ---- | A |   |
| BOE        | ---- | B |   |
| CMO        | ---- | C |   |
| Toppoly    | ---- | F |   |
| Hannstar   | ---- | H |   |
| Hitachi    | ---- | I |   |
| LG Philips | ---- | L |   |
| PVI        | ---- | P |   |
| RIT        | ---- | R |   |
| Tianma     | ---- | T |   |
| Varitronix | ---- | V |   |
| Unvision   | ---- | U |   |
| Kyocera    | ---- | K |   |
| Ness       | ---- |   | N |
| Sharp      | ---- |   | S |
| CPT        | ---- |   | Z |

(E) Resolution:

|       |     |   |     |   |
|-------|-----|---|-----|---|
| /     | 64  | X | 48  | L |
| /     | 80  | X | 48  | A |
| /     | 96  | X | 36  | B |
| /     | 96  | X | 64  | C |
| /     | 96  | X | 96  | D |
| /     | 101 | X | 80  | I |
| /     | 128 | X | 33  | M |
| /     | 128 | X | 64  | K |
| SQCIF | 128 | X | 96  | E |
| QCIF  | 176 | X | 220 | F |
| /     | 128 | X | 128 | G |
| /     | 160 | X | 120 | J |
| QQVGA | 160 | X | 128 | H |



|                  |        |   |     |   |
|------------------|--------|---|-----|---|
| QVGA             | 320    | X | 240 | Q |
| /                | 480    | X | 234 | R |
| /                | 480    | X | 220 | N |
| /                | 480    | X | 468 | O |
| VGA              | 640    | X | 480 | V |
| WVGA             | 800    | X | 480 | W |
| WQVGA            | 400    | X | 240 | W |
| /                | 800    | X | 600 | K |
|                  | Others |   |     | Z |
| (F) IC Supplier: |        |   |     |   |
| ILI              | ----   |   |     | I |
| Sitronix         | ----   |   |     | S |
| LG               | ----   |   |     | L |
| NT               | ----   |   |     | N |
| HIMAX            | ----   |   |     | H |