



1. ALL DIMENSIONS ARE IN mm WITH ± 0.20 TOLERANCE UNLESS OTHERWISE SPECIFIED
2. VIEWING ANGLE: 6:00 O'CLOCK
3. POLARIZER TYPE: TRANFLECTIVE, POSITIVE
4. DISPLAY TYPE: DFSTN
5. OPERATING VOLTAGE: 3V
6. DRIVE MOKE: 1/33 DUTY, 1/6 BIAS
7. OPERATING TEMPERATURE: $-10^{\circ}\text{C} \sim +60^{\circ}\text{C}$
8. STOPAGE TEMPERATURE: $-20^{\circ}\text{C} \sim +70^{\circ}\text{C}$
9. CONNECTOR: COG ST7565

PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14
DESC	VDD	C86	VSS	V0	V4	V3	V2	V1	CAP2+	CAP2-	CAP1-	CAP1+	CAP3-	VOUT
PIN	15	16	17	18	19	20	21	22	23	24	25	26	27	28
DESC	VSS2	D7	D6	D5	D4	D3	D2	D1	D0	RD(E)	WR(R/W)	A0	/RES	/CS1

TEL : 0755-25324802 FAX : 0755-36808262

Dwg Title				COG12832A			
Dwg No.			Date			2005-10-18	
Scale	Unit	Tol.		mm		±0.2	
Dro.wn		Checked		Approved			
DDU							