



- NOTES:**
- |                           |                         |
|---------------------------|-------------------------|
| 1. DISPLAY TYPE:          | FSTN                    |
| 2. OPERATING VOLTAGE:     | 3.0V                    |
| 3. OPERATING TEMPERATURE: | -10 C~60 C              |
| 4. STORAGE TEMPERATURE:   | -20 C~70 C              |
| 5. DRIVE MODE:            | 1/32D,1/6B              |
| 6. VIEWING DIRECTION:     | 6:00                    |
| 7. POLARIZER TYPE:        | TRANSFLECTIVE, POSITIVE |
| 8. CONNECTOR:             | COG/ST7565R or EQU      |
| 9. CUSTOMER No.:          |                         |

PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
SYMBOL	NC	NC	NC	NC	NC	NC	NC	NC	CS1	CS2	RES	A0	WR	RD	D0	D1	D2	D3	D4	D5	D6	D7	OUTY0	OUTY1	VDD
PIN	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48	49	
SYMBOL	VDD2	VSS	VOUT	NC	CAP3+	CAP1-	CAP1+	CAP2+	CAP2-	VEXT	VRS	V1	V2	V3	V4	V0	VR	M/SCLS	CB6	P/S	NC	NC	NC		

TEL : 0755-25324802 FAX : 0755-36808262

Dwg Title: **COG13232R**

Dwg No. \_\_\_\_\_ Date: 2005-10-18

Scale \_\_\_\_\_ Unit: mm Tol: ±0.2

Drawn: LIU Checked: \_\_\_\_\_ Approved: \_\_\_\_\_